

NEW PARTS FOR FRS / BRZ / 86

## WIDE TREAD LOWER FRONT ARM

965 462 A - \$800 MSRP



- \* High Strengthen steel pipe can handle maximum impact from racing compound tires.
- \* Possible 3 step negative camber settings.
  - 0mm, + 5mm, + 10 mm, [ + 15 mm : not with stock tie rod end]
- \* Hard rubber bushing eliminates alignment changes and provide precise steering response.
- \* Direct replacement for OEM lower arm
  - Bolt on installation: 1.0 hr. \*\*does NOT include alignment time
- \* Additional negative camber can result better tire contact patches and cornering speed.
- \* Extending lower arm length provide wider treads resulting higher front turning capacity.
- \* Unlike wheel offsetting, wider tread behavior can be achieved without effecting kingpin offsets or scrub radius.
- \*CUSCO adjustable pillow upper mount can be used for greater adjustments.

## [ Camber Data Example ]

\* Results will vary

Ride height: - 15mm from stock height Shock top location: Same as stock

Set Toe: 0 mm

LENGTH CAMBER DEG. <1> 0 mm = - **0.6** degree <2> + 5 mm = - 1.0 degree = - 1.5 degree <3> + 10 mm

<4> + 15 mm = - 2.0 degree





Not Applicable at  $\pm 15$ mm position when using OEM tie rod end. Make sure there is more than 20 mm for screws to contact at tie rod ends.





<sup>\*</sup> Additional data is available on request \* For Race use only, Do NOT use on public street. \* Make sure non of the part is contacting other parts.